




INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)



The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Best Available Copy

Signed

Dated 20 August 2004



THE PATENT OFFICE
WM

24 SEP 2003

Request for grant of a patent

(See the notes on the back of this form or on the explanatory leaflet from the Patent Office to help you fill in this form.)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

Fee: £0

24SEP03 E839637-1 D01631

P01/7700 0.00-0322361.7

1. Your reference

SJNG/46701.GB01

2. Patent application number
(The Patent Office will fill in this part)

24 SEP 2003

0322361.7

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ALTANA Pharma AG
Byk-Gulden-Strasse 2
D-78467
Konstanz
Germany

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of incorporation

Germany

844875001

4. Title of the invention

Compliance Monitor and Method

5. Full name, address and postcode in the United Kingdom to which all correspondence relating to this form and translation should be sent

Reddie & Grose
16 Theobalds Road
LONDON
WC1X 8PL

91001

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application
(if you know it)

Date of filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form

Description	12	/
Claim(s)	4	/
Abstract	1	/
Drawing(s)	6	/

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application

Signature

Reddie & Grose

Date

24 September 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

S J N GOODMAN

01223 340200 360350

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 10 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Patents Form

0080916 24-Sep-03 04:15

DUPLICATE

- 1 -

Compliance Monitor and Method

The invention relates to a compliance monitor and method for a drug delivery device.

Many types of drug delivery device are used by patients, or users, without continuous supervision by a physician or medical practitioner. For example, an asthma inhaler may be provided by a physician to a user, for the user to take doses either according to a predetermined schedule or when necessitated by the user's symptoms. It is then difficult for the physician to monitor the user's use of the drug delivery device and what dosage they have taken.

One type of inhaler is a pressurised metered dose inhaler (PMDI) as described in patent application WO 98/52542, which describes the Ciclesonide MDI device and formulation.

Summary of Invention

The invention provides a compliance monitor and method as defined in the appended independent claims. Preferred or advantageous features of the invention are set out in dependent sub-claims.

The invention may thus advantageously provide a compliance monitor which is attachable to, or forms part of, a drug delivery device, and which stores a compliance record indicating for each delivery of a dose of a drug or medicament from the device whether the device was properly positioned for administration of the drug. Proper positioning may vary depending on the device and the drug; for example for an orally or nasally administered drug, proper positioning is positioning of the device in or near

- 2 -

the user's mouth or nose. For delivery on or through the skin, proper positioning would be in contact with or near the skin.

In a preferred embodiment, the invention may thus
5 advantageously provide a compliance monitor for a drug delivery device for administering a drug orally, comprising a processor coupled to a switch, a sensor and a clock. The switch is actuatable by a user on delivering a dose from the drug delivery device. Advantageously, the
10 switch may be arranged so that operation of the drug delivery device by the user automatically actuates the switch. The sensor enables the compliance monitor to detect whether the device is positioned in the user's mouth during delivery of the dose. For example, the
15 sensor may detect mouth temperature or conductivity, or may detect a drop in light level, as a mouthpiece of the drug delivery device is inserted into the mouth.

When the switch is actuated, the processor records the time, as output by the clock, and records whether or not
20 an output from the sensor indicates that the device was properly positioned in the user's mouth during delivery of the dose. If delivery of a dose is indicated by actuation of the switch but the sensor output suggests that the mouthpiece of the device was not in the user's mouth, it
25 may be assumed that the dose was not properly delivered, as may happen, for example, if the device is accidentally actuated.

Preferably, data (the compliance record) from the compliance monitor may be downloaded to a docking station
30 or a computer for analysis, for example by a prescribing physician or medical practitioner.

- 3 -

In a further aspect, the invention may provide a method for monitoring use of a drug delivery device by using a compliance monitor, comprising the steps of determining (1) whether or not the device is properly positioned in contact with or relative to the user's body for administration of a drug or medicament whenever the device is operated to deliver a dose of the drug, and (2) storing in a compliance record an indication of whether or not the device was properly positioned in the user's mouth at each operation of the device.

The drug delivery device may advantageously be for oral drug administration, and is preferably an inhaler, for example for delivering a medicine or drug such as for the treatment of asthma. Such an inhaler may comprise or house a pressurised canister containing the drug and a propellant, so that depression of the canister within the drug delivery device delivers a dose of the drug. In a preferred embodiment of the invention, the switch is arranged so that it is easily, or automatically, actuated by the user on depressing the canister.

The compliance monitor may advantageously be removably attachable to the drug delivery device. It should be attachable to the drug delivery device so as not to interfere with or affect the performance of the device in delivering the drug. (This should similarly be the case if the compliance monitor forms part of the drug delivery device or is non-removably attachable to it.) A device such as an inhaler must undergo strict appraisal before it is approved for public use, and the compliance monitor should be designed so that attaching it to or integrating it with such a drug delivery device should not require reappraisal of the device. Thus, the compliance monitor should, in the case of an inhaler, advantageously attach

- 4 -

to the exterior of the inhaler and have no components which modify or interfere with the depression of the pressurised canister or the air or gas flow path through the inhaler.

- 5 Thus, in a preferred embodiment, the invention provides a compliance monitor which attaches to the base of an inhaler casing and in which the sensor is located on an exterior surface of the inhaler mouthpiece.

- 10 In addition, the compliance monitor actuation switch should preferably not interfere with or alter normal operation of the drug delivery device. For example, when attached to an inhaler, the switch may be positioned at the base of the inhaler housing so that a user may operate the inhaler by applying a finger to the upper end of the
- 15 canister, typically at the top of the inhaler, and a thumb to the switch at the base of the inhaler.

The sensor is preferably a temperature sensor.

- Advantageously, the processor takes a temperature reading from the sensor at regular intervals, typically of between
- 20 0.1 and 1.0 seconds, for example every 0.2 seconds. (The sampling rate may be temporarily increased when the switch is actuated.) The processor may thus detect insertion of the inhaler into the user's mouth by sensing a rapid change in temperature towards the mouth temperature.
- 25 Optionally, the processor may subsequently confirm that the drug delivery device was placed in the user's mouth by monitoring a change in temperature away from the mouth temperature when the device is removed from the mouth after delivery of a dose.

- 30 A rate of change of temperature towards and/or away from the mouth temperature may also be used to detect insertion

- 3 -

of the drug delivery device into the mouth. The processor may also monitor ambient temperature, as measured by the temperature sensor before and after insertion into the mouth, and take account of the ambient temperature when
5 determining whether or not the device was properly placed in the mouth when the dose was delivered.

The sensor may alternatively be a light sensor. The processor would then detect insertion of the drug delivery device into the mouth by looking for a characteristic
10 change in light level.

The sensor may alternatively be a conductivity sensor, for sensing a characteristic mouth conductivity when the drug delivery device is inserted into the mouth.

Alternatively, a combination of such sensors may be used.

15 Whichever type of sensor is used, it should advantageously be positioned externally to the drug delivery device mouthpiece so as not to interfere with operation of the device.

According to a further aspect of the invention, after a
20 period of time such as a few days or weeks, or up to a few months or more, the compliance monitor may be coupled to a docking station or a computer to download the compliance record, for example for review by a physician or medical practitioner. The record comprises for each delivery of a
25 dose an indication of whether the drug delivery device mouthpiece was properly placed in the user's mouth. It may also include the times at which doses have been delivered. The physician may thus determine when doses have been properly taken and when doses have been
30 delivered incorrectly, for example into free air, whether

- 6 -

by accidental or malicious operation of the device. The physician may thus assess the dosage actually taken by the user. Where regular doses of drug are to be taken according to a prescription, the physician may thus assess
5 whether the user has followed the prescription. Where doses of a drug are taken in response to symptoms, the physician may assess what dosage or dosage frequency the user has required. Often, the physician may not know if a user's continuing illness is due to not taking a drug in
10 the prescribed manner or because the drug is not effective. The compliance monitor may report when the drug is properly used so that the physician may discover whether the user is using the drug as prescribed.

In a preferred embodiment, the compliance monitor
15 comprises a low-power microprocessor with timing capability and memory storage to record multiple uses of the drug delivery device. The sensor is a separate component which provides an analogue input to the microprocessor, sensitive to mouth temperature or
20 conductance, or light level, as described above. The monitor is advantageously effectively permanently switched on, so that the user does not have to intervene with monitor operation. The monitor advantageously comprises the microprocessor and other components housed in a small
25 enclosure which is affixed to the drug delivery device, for example by means of a clip, an adhesive, or an adhesive label. Advantageously, the monitor is relatively unobtrusive when fastened to the device.

- 7 -

Description of Specific Embodiments and Best Mode of the
Invention

Specific embodiments of the invention will now be
described by way of example, with reference to the
5 attached drawings in which;

Figure 1 is a longitudinal section of a standard
pressurised metered dose inhaler (PMDI);

Figure 2 is a perspective view of the PMDI of Figure 1;

Figure 3 is a side view of the PMDI of Figure 1 having a
10 compliance monitor according to a first embodiment of the
invention fastened thereto;

Figure 4 is a perspective view from beneath the compliance
monitor and PMDI of Figure 3;

Figure 5 is a cross section of the compliance monitor of
15 Figure 3;

Figure 6 is a front view of a docking station according to
a further embodiment of the invention for receiving the
compliance monitor and inhaler of Figure 3;

Figure 7 is a front view of the docking station of
20 Figure 6 with the compliance monitor and PMDI in place;
and

Figure 8 is a block diagram of the circuitry of the
compliance monitor and docking station.

Figure 1 is a longitudinal section of a conventional
25 pressurised metered dose inhaler (PMDI), in which a

- 8 -

moulded plastics housing 2 comprises a cylindrical portion for receiving a pressurised canister 6, and a mouthpiece 8. The pressurised canister contains a drug and a propellant gas. When the canister is depressed into the housing by a user, the drug is expelled from a nozzle 10. At the same time, the mouthpiece is inserted into the user's mouth, and the user inhales to take a dose of the drug in known manner.

Figure 2 is a perspective view of the PMDI, showing a generally bevelled, or cut-away, portion 12 of its exterior surface opposite the mouthpiece, at the base of the cylindrical portion opposite the exposed end of the canister which is depressed by the user.

Figures 3, 4 and 5 illustrate a compliance monitor embodying the invention. This comprises a moulded rubber housing 20 comprising an interface surface 22 shaped to abut the bevelled, or cut-away, portion 12 of the PMDI exterior. Advantageously, the interface surface clips onto the PMDI, but alternatively an adhesive or an adhesive label may be used to securely fasten the compliance monitor to the PMDI.

Figures 3 and 4 illustrate the compliance monitor in position on the PMDI. Figure 5 shows the monitor in cross section.

Within the rubber housing are mounted a battery 24, a switch 26, an electronics module 28, a temperature sensor 30, and a set of contacts 32. The battery, electronics module, switch and contacts are mounted on a printed circuit board 34 and the temperature sensor is mounted at the end of a protruding portion 36 of the rubber housing which extends, in use, along an underside

- 9 -

of the PMDI mouthpiece so that the temperature sensor enters or contacts the user's mouth when the mouthpiece is placed in the mouth. The rubber housing adjacent to the temperature sensor is sufficiently thin to allow rapid
5 heat conduction from the mouth to the sensor.

The switch 26 is covered by a flexible portion 38 of the rubber housing, to enable the switch to be depressed. The contacts 32 are covered by an openable portion 40 of the rubber housing which can be removed or opened when the
10 compliance monitor is placed in a docking station as described below.

Figure 6 is a front view of the docking station 50 comprising a cradle 52 for receiving the compliance monitor attached to the inhaler. A set of electrical
15 contacts 54 connects with the contacts 32 of the compliance monitor when docked. The docking station comprises a display 56 and control buttons 58 for use to review data downloaded from the compliance monitor.

Figure 7 illustrates the compliance monitor and PMDI
20 docked in the docking station 50.

Figure 8 is a block diagram of the electronic circuitry of the compliance monitor and the docking station, connected by their respective contacts 32, 54.

The electronics module 28 of the compliance monitor
25 comprises a processor 60 coupled to the contacts 32 and the switch 26 and, at an analogue input, to the temperature sensor 30. The battery 24 powers the electronics module.

- 10 -

Within the electronics module, the processor is coupled to a memory 60 and a clock 62.

The docking station 50 comprises a processor 64 coupled to the contacts 54, the display 56 a memory 66 and a
5 clock 70. The processor is controlled by means of the control buttons 58. The processor is also coupled to an interface 68, which is couplable to an external device such as a computer. The interface 68 may be, for example, a USB port or other standard interface.

10 When the compliance monitor is docked with the docking station, the docking station processor can interrogate the compliance monitor processor and download stored data into its own memory 66. The data can then be processed and
15 displayed on the display screen 56 under the control of a medical practitioner through use of the buttons 58. Data downloaded from the compliance monitor is timed, using the compliance monitor clock, but this clock may not be synchronised with real time. Therefore, the clock 70 in
20 the docking station, which is synchronised with real time, enables the data to be timed and date stamped after downloading.

An object purpose of the compliance monitor of the embodiment is to allow a physician or other medical practitioner to monitor usage of a drug delivery device
25 such as an inhaler, or PMDI, used to treat conditions such as asthma where the regular and accurate taking of medication is necessary to treat the condition. To this end, the physician clips the compliance monitor 20 on to the PMDI body 2 and activates the monitor by connecting
30 the battery. The combined monitor and PMDI are then supplied to the user, or patient, in the normal way.

- 11 -

When the user requires medication, he inserts the mouthpiece 8 into his mouth, inhales and simultaneously depresses the upper end of the pressurised canister 6 in known manner. This causes a unit dose of medication to be released and drawn by the user's breath through the mouthpiece. The compliance monitor switch is positioned on the base of the monitor such that the user can hold the monitor between finger and thumb and, while depressing the upper end of the canister, simultaneously press on the switch. The switch is positioned so that this happens automatically if the user grips the inhaler between finger (on top of the canister) and thumb (at the base of PMDI housing) in the normal way. Closure of the switch tells the processor 60 that the PMDI has been operated.

The processor 60 regularly monitors the ambient temperature close to the PMDI mouthpiece by means of the sensor 30. For example, the temperature may be monitored at intervals of between 0.1 seconds and 0.5 seconds, or 1.0 seconds. When the mouthpiece is inserted into the user's mouth, the sensor will detect a rapid temperature change and this is signalled to the processor. Thus, a coincidence between sensing canister actuation (by means of the switch) and a rapid temperature change is taken to indicate that the drug has been delivered with the PMDI mouthpiece in the user's mouth and not, for example, in free space. This information is stored in the compliance monitor memory 60 along with a time from the clock 62.

The user continues to use the PMDI for a period determined by the physician. At the end of this time, they return the device to the physician. The physician then docks the monitor in the docking station and the stored data is transferred under control of the docking station processor 64, to the docking station memory 66. This

process is initiated by pressing one of the buttons 58 on the docking station.

5 The docking station's real time clock 70 enables the dosage times recorded by the compliance monitor to be converted to real times after the data has been downloaded. The data can then be presented on the docking station display in a number of forms such as the time of each event and whether the event is associated with a temperature change corresponding to the device mouthpiece
10 in the patient's mouth. Alternatively, a statistical survey of the data can be given, such as an indication of whether doses have been taken regularly.

The buttons 58 allow the data to be scrolled on the display.

15 Data can also be outputted to an external device such as a computer, PC or printer through the interface 68, for example for further analysis or for remote monitoring by a physician.

Claims

1. A compliance monitor for a drug delivery device for administering a drug, comprising:

a switch actuatable by a user on delivering a dose
5 from the device;

a sensor for detecting whether the device is properly positioned in contact with or relative to the user's body for delivery of the dose; and

a processor coupled to the switch and the sensor for
10 recording whether or not the device was properly positioned when the switch was actuated.
2. A compliance monitor according to claim 1, which does not affect the normal operation of the drug delivery device.
- 15 3. A compliance monitor according to claim 1 or 2, which is removably attachable to the drug delivery device.
4. A compliance monitor according to any preceding claim, comprising a clock coupled to the processor and in which the time of actuation of the switch is
20 recorded.
5. A compliance monitor according to any preceding claim, ~~proper positioning of the drug delivery device~~
being positioning in contact with or relative to the user's mouth, nose or skin, as appropriate for
25 administration of the drug.

- 14 -

6. A compliance monitor according to any preceding claim, the drug delivery device being for topical administration of the drug.
- 5 7. A compliance monitor according to any preceding claim, the drug delivery device being for oral administration of the drug, preferably by inhalation.
8. A compliance monitor according to any preceding claim, the drug delivery device being an inhaler operated by the user depressing a pressurised
10 canister containing the drug, and in which the switch is a pressure-operated switch actuatable as the user depresses the canister.
9. A compliance monitor according to any preceding claim, the drug delivery device being a dry powder
15 inhaler, a pressurised metered dose inhaler or a nebuliser.
10. A compliance monitor according to any preceding claim, in which the sensor is a temperature sensor for sensing body temperature, for example mouth
20 temperature.
11. A compliance monitor according to any preceding claim, in which the sensor is a light sensor for sensing when the sensor is covered, for example by the mouth.
- 25 12. A compliance monitor according to any preceding claim, in which the sensor is a conductivity sensor for sensing body conductivity, for example mouth conductivity.

- 15 -

13. A compliance monitor according to any preceding claim, in which a change in an output of the sensor characteristic of correct use of the drug delivery device is used to determine whether the device was properly positioned when the dose was delivered.
14. A compliance monitor according to any preceding claim, further comprising an output for downloading data to a docking station or a computer.
15. A compliance monitor according to any preceding claim, in which the data comprises a compliance record of use of the drug delivery device, including a record of whether the sensor output indicates that the device was properly positioned on each occasion that a dose has been delivered.
16. A docking station for use with a compliance monitor as defined in any of claims 1 to 15.
17. A computer-readable medium carrying a computer program for programming a general purpose computer to receive and process data downloaded from a compliance monitor as defined in any of claims 1 to 15.
18. A drug delivery device comprising a compliance monitor as defined in any of claims 1 to 15.
19. A method of using a compliance monitor to monitor use of a drug delivery device for administration of a drug, comprising the steps of;
- determining when a user operates the device to deliver a dose of the drug;

- 16 -

sensing whether the device is properly positioned in contact with or relative to the user's body when the dose is delivered; and

5 recording for each operation of the device whether or not the device was properly positioned.

20. A method according to claim 19, further comprising the step of determining and recording the time of each operation of the device.

10 21. A method according to claim 19 or 20, in which the drug delivery device is for oral administration of the drug and proper positioning of the device is proper positioning in the user's mouth.

15 22. A method according to claim 19, 20 or 21, further comprising the step of downloading recorded data from the compliance monitor to a docking station or a computer to allow a compliance record to be reviewed, for example by a medical practitioner.

23. A compliance monitor substantially as described herein, with reference to the drawings.

20 24. A compliance monitoring method substantially as described herein, with reference to the drawings.

- 17 -

Abstract

(Figure 4)

Compliance Monitor and Method

5 A compliance monitor 20 is attachable to or forms part of
a drug delivery device, such as an inhaler 2. The monitor
comprises a switch 38 which is actuated by a user when
delivering a dose of medicament. The monitor further
comprises a sensor for sensing whether the device is
10 properly positioned in contact with or relative to the
user's body for administration of the medicament. For
example, where the device is an inhaler and the sensor a
temperature sensor, temperature variations caused by
insertion of an inhaler mouthpiece into the user's mouth
15 indicate whether the dose has been delivered into the
patient's mouth. A memory in the compliance monitor
stores a compliance record indicating whether or not the
device was properly positioned each time a dose was
delivered.

1/6




FIGURE 1

2/6




FIGURE 2




FIGURE 3





FIGURE 4

3/6



4/6




FIGURE 6

5/6




FIGURE 7

6/6




FIGURE 8

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.